

Rubiomonocoat UNIVERSAL MAINTENANCE OIL



DESCRIPTION:

Rubio Monocoat Universal Maintenance Oil is a universal maintenance oil that can be used to both refresh the color and protect oiled wood surfaces. The frequency of maintenance depends entirely on the intensity of use of the floor. It is recommended to perform this treatment before the color fades. **RMC Universal Maintenance Oil** maintains the wood, gives it a fuller appearance (satin sheen) and makes it more resistant to liquids. Maintenance with **RMC Oil Plus 2C** in the original color is recommended when excessive wear or damage is visible on the treated surface, or the color needs to be restored.

INSTRUCTIONS FOR USE:

Treatment with **RMC Universal Maintenance Oil** can be carried out without any prior technical knowledge.

1. Clean the floor from dirt and dust.
2. Clean the floor thoroughly with water and **RMC Soap**. Wipe well with water to remove all soap residues. Allow to dry dry well.
3. Manual application: Apply oil with a cloth, brush or sponge. Machine application: Apply oil with a machine (beige pad). Preferably proceed in zones of 2 to 4 m² each. The treated areas must be wiped with kitchen paper or a cotton cloth within 15 minutes. When using a floor polisher: Dry the floor with a white pad.
4. Ensure sufficient ventilation so that the floor can dry well. Duration: approx. 6 - 8 hrs.

During the first week, clean only with a damp cloth. After that, the floor can be cleaned with **RMC Soap**.

CONSUMPTION:

0,5 liter = 75 to 100 m². (according to the wear)

Use very little product to avoid the floor becoming sticky.

The data of these consumption values are indicatif. Results depend on wood type and preparation method. For an exact determination of the consumption we recommend the use of a dipstick.

TECHNICAL SPECIFICATIONS:

Product: mixture of neutral oils

Consistency: Liquid

Flash point: Cc (astm d93) : > 65 °C

Density: 0,93 -1,4 g / cm³

VOC percentage: 0 g/L

STORAGE:

The product can be stored for 12 months. Storage must be under dry conditions and in the original packaging.

PACKAGING:

0.5 liter can

ATTENTION:

**Product must not be diluted under any circumstances!
Cloths soaked with the product may self-ignite and must be
neutralized in water after use.**

YOUR DISTRIBUTION PARTNER:

LIABILITY: It is the responsibility of the user to determine by his own tests whether the product is suitable for the chosen application. In no event shall Muylle-Facon NV be liable for any consequential damages. The above information may be subject to updates which will be announced in the revised versions of the technical data sheet. technical data sheet. We cannot be held responsible for poor results due to causes other than the quality of the product. This technical information has been prepared based on current information and knowledge. The latest technical data sheets can be requested or are available on the website.



See safety data sheet before use. Date of
TBD: 22/08/16

MUYLLE FACON



MADE IN BELGIUM by N.V. MUYLLE - FACON S.A.
Ambachtenstraat 58 - B-8870 Izegem (Industriezone Abele)
Tel. +32 (0)51 30 80 54 - Fax + 32 (0)51 30 99 78 - HRK 1823
info@muyllefacon.be - www.rubiomonocoat.com

